



 pezzolato

Drum Chipper **PTH 40.70 MULTICUT** Serie

*Wood chipper with multi-knivessystem drum
and big feeding hopper*

GREENLINE

PTH 40.70 MULTICUT



PTH 40.70 MULTICUT

PTH 40.70 MULTICUT joins to the established range of Pezzolato's drum chippers with closed drum. It's a drum chipper equipped with "open" drum on which are mounted eight knives. This cutting system can reach high trunk's diameters requiring not excessive powers. The machine keeps the particularly robust structure of Pezzolato's drum chippers, ensuring reliability

and excellent performances. The amplitude of the loading mouth, the maximum inlet passage is 640 x 400 mm, allows to introduce easily voluminous material by mechanical means.

The loading mouth is resealable to give greater compactness to the machine during transport. For manual feeding the chipper is equipped with a robust safety bar that provides safety



Space saving during transportation



Big feeding hopper



using the machine. A large horizontal roller with pawls supported by a belt placed in the inner part of the hopper allow to insert the material easily.

The electronic device "No stress" with counter hours, automatically regulating the in-feed of material according to the available power. The calibration grid is interchangeable and allows to define the chip size and ensures that chip is

uniform and homogeneous. The fan with a large diameter allows to eject the chips through the discharge

pipe fitted, at the end, of adjustable deflector. It can be powered by the PTO tractor or by autonomous engine (Diesel, electric). The possible arrangements are: stationary, low or high speed trailers, 3 point hitch attachment.



Multi-knives system drum



These chippers guarantees the production of calibrated chips

EXTRAS AND CONFIGURATIONS

- NO STRESS electronic device**, available on all standard machines, automatically regulates the in-feed of material according to the available power
- Recovering collecting screws**, with different size holes, easy to replace
- Radio or cable remote control**, to manage the chippers main activities at a distance
- Removable security bar**, for hand or crane feeding
- Hydraulic orientation** (deflector rotation and direction) **discharge tube**
- Low- or high-speed towing trailer**, with air or hydraulic brakes
- Forestry cranes, with or without cabin**, in customized configuration
- Stationary version with electric motor**
- Feeding chain along the entire hopper** to make easier the feeding with bulky material
- Hydraulic traction**, to easily move the machine in impervious paths
- Discharge belt**, to obtain better quality chips



TECHNICAL DATA		PTH 40.70 MULTICUT
Maximum chipping diameter (soft wood)	mm	400
Maximum chipping diameter (hard wood)	mm	300
Drum width	mm	640
Drum diameter	mm	520
Maximum inlet passage	mm	640 x 400
Knives	n°	8
Hourly throughput	m ³ /h	15 - 20
Minimum tractor power	Hp	70
Maximum tractor power	Hp	130
Weight PTO machine (std model)	Kg	2900



DEALER