

# 20/25 tm

# Diesel

### Portata a 0,7 m dallo scudo

Lifting capacity at 0,7 m from front plate  
Capacité de levage à 0,7 m de la plaque avant  
Tragfähigkeit: 0,7 m vor dem Kran

DIN 25 t / SAE 27,5 t

### Trazione

Drive / Traction / Antriebe

Anteriore / Front / Avant / Front

### Motore Diesel

Diesel engine / Moteur Diesel / Diesel-Motor

107 kW

### Velocità massima

Max. speed  
Vitesse maxi.  
Höchstgeschwindigkeit

27,50 km/h

### Pneumatici

Tyres / Pneus / Räder

12.00-24

### Capacità pneumatico singolo

Capacity of each tyre  
Capacité du pneu  
Reifentragfähigkeit

max. statica

max.static / maxi.statique / stillstand max.

12420 kg

### Altezza braccio

Boom height  
Hauteur de la flèche  
Auslegerhöhe

13 m

### Sbraccio utile

Working outreach  
Rayon de travail  
Auslegerlänge vor dem Kran

7,7 m

### Inclinazione braccio

Boom angle  
Angle de la flèche  
Auslegerwinkel

- 9° + 60°



### Stabilità assicurata da quattro punti di appoggio

Four contact points assure stability  
Stabilité Assurée par 4 points d'appui  
Stabilitätssicherheit durch 4 Stützpunkte

### Omologazione Stradale

Road certification  
Homologation routière  
Straßenzulassung



