

# 50/55 tm

# Diesel

## Portata a 1 m dallo scudo

Lifting capacity at 1 m from front plate  
Capacité de levage à 1 m de la plaque avant  
Tragfähigkeit: 1 m vor dem Kran  
DIN 50-55 t / SAE 55-60 t

## Trazione

Drive / Traction / Antriebe  
Anteriore / Front / Avant / Front

## Motore Diesel

Diesel engine / Moteur Diesel / Diesel-Motor  
210 kW

## Velocità massima

Max. speed  
Vitesse maxi.  
Höchstgeschwindigkeit  
25 km/h

## Pneumatici

Tyres / Pneus / Räder  
16.00-25

## Capacità pneumatico singolo

Capacity of each tyre  
Capacité du pneu  
Reifentragfähigkeit

max. statica  
max.static / maxi.statique / stillstand max.  
22500 kg

## Altezza braccio

Boom height  
Hauteur de la flèche  
Auslegerhöhe  
15 m

## Sbraccio utile

Working outreach  
Rayon de travail  
Auslegerlänge vor dem Kran  
9 m

## Inclinazione braccio

Boom angle  
Angle de la flèche  
Auslegerwinkel  
- 7° + 58°



## Stabilità assicurata da quattro punti di appoggio

Four contact points assure stability  
Stabilité Assurée par 4 points d'appui  
Stabilitätssicherheit durch 4 Stützpunkte

## Omologazione Stradale

Road certification  
Homologation routière  
Straßenzulassung



