



## Ampliroll® AL20 PA

## Key points



Versatile equipment that lifts more bodies

Optimize the loading angle

Operation under low roof height

Rear hydraulic body locking

Casting hook with pneumatic safety latch

Free tilting frame that acts as a power multiplier

Integrated dashpot in main cylinders

Pre-drilled subframe

## Marrel telescopic and articulated range

Truck GVW from 26 to 32T			S48	S49	S50	S51	S52	S53	S54	S55	S56	S57	S58	S59	S60
	Container length : min	LG mm	3200	3200	3200	3200	3500	3500	3500	3800	3800	3800	3800	3800	4000
	max		5900	6000	6100	6200	6300	6400	6500	6600	6800	6900	7000	7100	7200
	Container with fixed underide		5300	5400	5500	5600	5700	5800	5900	6000	6100	6200	6300	6400	6500
	Own weight	Kg	2330	2335	2335	2340	2460	2460	2465	2485	2510	2515	2515	2520	2535

## Standard configuration

### Hooklift with telescopic and articulated jib

- Lifting capacity 20 tons, tested with 24000 loading cycles
- Mini and maxi body length are determined by the pre-study drawing
- Hook height: 1425 mm
- **Casting lifting hook equipped with pneumatic safety latch, welded on**
- Advanced free tilting frame acting as lifting power multiplier
- Installation height assures an optimum position of container's CG
- 4 supports with external centering + 2 additional supports (depending of the unit length)
- **Subframe drilled all over the length for a complete bolted installation**
- Rear roller with large flanges mounted one tipping axis, suited for bodies with longitudinal runners spaced at 1.060 mm
- Hydraulic container external locking device, low installation and cover plate
- Safety while tipping : telescopic jib and rear hydraulic locking cannot be operated
- Directional valve equipped with manual socket, piloted by pneumatic ON/ OFF controls in cab and signal light box
- **Integrated dashpot for retracting the main lifting cylinder**
- One check valve flanged for two main cylinders and non-return valve on all hydraulic cylinders
- Sidebox with all hydraulic- pneumatic and electrical functionalities
- The equipment are assembled and tested in factory.
- Equipment is painted in dark primer

### Hydraulics

Hydraulic cylinders manufactured by Marrel

Integrated dashpot : slows the main cylinders

Check valve for main cylinder

Safety device to prevent miss-use of the equipment

### Mechanical structure

Steel with high tensile strength

Casting parts used for critical functions

Welding by robot welders and machining of the articulations

**Anti-corrosion treatment** : grinding of all mechanical welding components

### Safety and container locking

Rear hydraulic body locking (outside and inside)

In operation outside warning buzzer

## Options and Accessories

- Additional hydraulic valves (for cranes, rear tipper trailer, ...)
- Fast speed operation (only for moving empty bodies)
- Front hydraulic body locking device
- Rear axle suspension blocking synchronized with rear lock
- Rear stabilizer with independant controls and warning light
- Electro-pneumatical cab controls, ...

- Oil tank to be installed on truck sides or behind the cab
- Attachments brackets suited for the various truck model
- Rear under ride bumper PANTO, tiltable or fixed
- Side protections fixed or tiltable mount
- Tool box and expandable net carrier
- Fire extinguisher box – Working light
- Aluminium fender, ...



Your Dealer



MARREL SAS  
Andrézieux-Bouthéon  
March 2016 – Ind. 01

