

F3 CO 10 C / 15 C . COLUMN TAIL-LIFT POWER OPENED/CLOSED PLATFORM - 2 CYLINDERS

LOAD CAPACITY

- 1000 KG
- 1500 KG



COLUMN
TAIL LIFTS



APPLICATIONS

F3 CO 10 C and F3 CO 15 C - lifting capacity 1000 kg / 1500 kg - is specifically recommended for vehicles weighing more than 3,5 tons.

Light but sturdy with columns (pillars) and platform designed and made entirely in aluminium.

TECHNICAL SPECIFICATIONS

Pillars:	Aluminium
Cylinders:	2 single acting
Main beam:	Steel
Platform:	Aluminium
Standard platform depths:	700 - 900 - 1050 - 1200 - 1350 (1800 mm on demand)
Tip depths:	300 mm
Standard control:	Unit Exterior fix control
Platform opening and closing with 1 hydraulic cylinder	



Tail-lift is always built according to customer's request.



Mod.	Load capacity (load centre of gravity at 600 mm)	Width over columns*	Width between columns	Column centers	Platform depth (std. platform)	E		D		Weight kg
						min	max	min	max	
F3 CO 10-15 C	1000 Kg 1500 Kg	2233 2538	2087 2392	2165 2474	900	900 1400	1400 1700	395	495	335

*Width over columns minimum 1934 mm (on demand)

Centre of gravity of the vehicle depending on the platform depth and the type of the installations on the vehicle (see assembly instructions). The above mentioned weights are approximate and may vary according to production. Anteo reserves the right to change weights and technical specifications without prior notice. No indemnity for damages can be claimed from Anteo for changes in technical specifications and/or in weight.

